



BARREL LENGTH

6.5" (165 mm) with 3 lug
OPTION: 6" (152,4 mm) with threaded
barrel, 1/2" - 28 special

CALIBER

.40S&W

ACCESSORIES

M-LOK (3h/6h/9h),
NATO PICATINNY RAIL

RATIO BETWEEN SIGHT

MAX 260mm

STOCK TYPE

Folded + Extended 4 positions

LENGTH

Folded buttstock: 382mm
Extended buttstock: 615mm
Extended 0 position: 570mm

BARREL GROOVES

To the right, 6 grooves, 406mm

SYSTEM

Delayed blowback system

RATE OF FIRE

Approx. 750±100 rounds/min

FIRING MODE OPTIONS

SAFE, SEMI-AUTOMATIC, FULL AUTO

FINISHING

Black matt

WIDTH

55mm
90±4mm (with folded buttstock)

WEIGHT

2,2±0,3 kg
2,3±0,3 kg with empty magazine

SIGHTS

Integrated or on the Picatinny rail

TRIGGER WEIGHT

2.5 - 3.5 kg

CHARGING HANDLE

AMBI / NOT CYCLABLE

MAGAZINES

30rd magazine polymer
(3 Mags per weapon)

HEIGHT

197±4mm (with magazine, without sights)
255±4mm (with magazine and sights)

SPRINGFIELD
ARMORY

X HS

KUNA SEMI-AUTO & FULL AUTOMATIC cal. 40S&W



KUNA SOUND SUPPRESSOR SI

CALIBER	.40S&W
MOUNTING SYSTEM	3-LUG
LENGTH	200 mm
DIAMETER	44 mm
WEIGHT	380 g
COLOUR	BLACK
FINISH	ANODIZED / QPQ TENIFER
SOUND REDUCTION	min 27 dB / max 30 dB
FULL - AUTO RATED	YES

