



HS

EXPECT THE BEST

Technical specifications:

		Assault rifle VHS-D2	Assault rifle VHS-D2 CT - 1.5X	Assault rifle VHS-K2	Assault rifle VHS-K2 CT - 1.5X
1	Caliber:	5.56 x 45 mm	5.56 x 45 mm	5.56 x 45 mm	5.56 x 45 mm
2	Operating principle:	gas operated short stroke piston	gas operated short stroke piston	gas operated short stroke piston	gas operated short stroke piston
3	Barrel length:	500 mm	500 mm	410mm	410 mm
4	Rate of fire:	850 ± 100 rd/min	850 ± 100 rd/min	830 ± 100 rd/min	830 ± 100 rd/min
5	Muzzle velocity:	910 ± 30 m/sec	910 ± 30 m/sec	880 ± 30 m/sec	880 ± 30 m/sec
6	Length (overall):	800 mm	800 mm	710 mm	710 mm
7	Length (with extended buttstock):	850 mm	850 mm	760 mm	760 mm
8	Width:	75 mm	75 mm	75 mm	75 mm
9	Height with carrying handle:	234 mm	250 mm	234 mm	250 mm
10	Height with magazine (30 rd):	297 mm	312 mm	297 mm	312 mm
11	Weight without magazine:	3,9 kg	4,3 kg	3,75 kg	4,15 kg
12	Weight of empty magazine:	139 g	139 g	139 g	139 g

Optical sight with red dot and magnification CT-1.5X

1	Magnification	1.5 x ± 0,05	1.5 x ± 0,05
2	Diameter	10 mm	10 mm
3	Visible field	5,1° ± 0,1°	5,1° ± 0,1°
4	Optimal distance from eye	70 ± 10 mm	70 ± 10 mm
5	Operating temperature	from -32°C to +49°C	from -32°C to +49°C
6	Storage temperature	from -40°C to +71°C	from -40°C to +71°C



Special features:

- Ambidextrous: firing selector, cocking handle, bolt catch release and magazine release.
- Selectable left/right cartridge ejection port.
- Adjustable multiple aperture rear sight for 100m/200m, 300m, 400m and 500m.
- Interchangeable magazine well with M16 magazine option.



VHS-2

cal. 5,56x45





VHS-2
cal. 5,56x45



VHS-K2



VHS-D2,
VHS-BG



VHS-D2,
CT-1.5X



VHS-D2,
VHS-BG,
CT-1.5X

THE VHS FAMILY OF MILITARY ASSAULT RIFLES