

HS

EXPECT THE BEST



HS-9 G3

Enhanced ergonomic and design



SEMI AUTOMATIC / SHORT RECOIL / STRIKER FIRED PISTOL



INDICATORS



FIRING PIN STATUS

Visual and tactile indicator for firing pin. When the firearm is cocked, the pin will protrude out of the rear of the slide.



LOADED CHAMBER

Visual and tactile indicator for barrel chamber. When the loaded chamber indicator is up the bullet is in the chamber.



GRIP SAFETY

Unless the grip safety is properly depressed and deactivated, the firearm will not fire even if the trigger is pulled.



FIRING PIN SAFETY




Does not allow the release of the firing pin without pulling the trigger.



TRIGGER SAFETY

Prevents unintentional moving of the trigger backwards.

TEXTURE DESIGN



1

2

3



HS-9 4.0" G3

Caliber	9x19
Barrel length	103,5 mm
Overall length	180,5 mm
Overall height	140 mm
Width	33 mm
Weight with empty mag.	785 g
Magazine capacity	16 rd
Line of sight	158 mm

Mirka Bogovića 7 | 47000 Karlovac | Croatia

Phone: +385 (0)47 666 666 | Fax: +385 (0)47 645 594

E-mail: hs-produkt@hs-produkt.hr | www.hs-produkt.hr

EXPECT THE BEST